

FTM

Flexible taping machine



Features and benefits

- Twin mast column for greater stability during operation
- Auto on/off- for power saving
- Digital carton counter
- Separate Top & Bottom Drive for perfect and uniform taping
- Uniform & controlled pressure during taping
- Twin Flap Squeeze Rollers provides additional squeezing for perfect top alignment
- Belt speed of 20 m/minute
- Inbuilt Tool Box- Ease of maintenance

SIGNODE®

Flexible taping machine

Technical Specifications

Machine Specification	FTM
Taping Head	Standard (2"/2.5"/3"), Flexible (2"/2.5")
Length	1590 mm(With 0.5 Mtr Conveyor)
Width	810 mmHeight1400 mm
Weight	155 Kg
Color	RAL 6000 & RAL 1021 Yellow (Moving Parts)
Drive Motor	0.25 HP, 2 No.
Belt speed	20 Metres/ Min
Machine Through put	Belt speed/(Carton length+280 mm)
Utility Requirements	
Air Requirement	NA
Air Consumption	NA
Power Supply	415 V AC, 3 Phase, 50 Hz
Power Consumption	0.36 KW
Tap Roll Length	65 M / 650 M/ 1000 M
Case Dimensions	
Length	150 mm - Un Limited
Width	160 mm -550 mm
Height	100 mm -550 mm
Weight	2- 50 Kg
Carton Ply	Min 3 Ply

User friendly

- Self-centering side guides for accurate centering
- Positive top and bottom drive to ensure sealing of tall and heavy cartons, in addition to regular cartons
- 500 mm extra conveyor at entry/ exit for ease of operation
- Telescopic legs for height adjustment

Safety

- Conformance with CE norms
- Emergency Stop Pushbutton
- Belt Guards for operator safety
- Optional MS(wire mesh) /Polycarbonate Safet Guards for additional safety

SIGNODE®

Your partner in industrial packaging world wide

E: info@signodeindia.com | W: www.signodegroup.com

Toll Free Number for Services 1800 419 1466